

Thuyết minh thông số kỹ thuật Switch Juniper EX2300-C-12T

Performance & Bandwidth thông số EX2300-C-12T Switch - L3 - managed - 12 x 10/100/1000 + 2 x Gigabit SFP / 10 Gigabit SFP+ - rack-mountable	
Mã	EX2300-C-12T
Product Description	Juniper Networks EX Series EX2300-C-12T - switch - 12 ports - managed - rack-mountable
Device Type	Switch - 12 ports - L3 - managed
Enclosure Type	Rack-mountable 1U
Subtype	Gigabit Ethernet
Ports	12 x 10/100/1000 + 2 x Gigabit SFP / 10 Gigabit SFP+
Performance	Switching capacity: 64 Gbps Throughput: 47 Mpps
Capacity	LAG groups: 128 Maximum member ports per LAG: 8 Multiple Spanning Tree Protocol instances: 64 ARP entries: 1024 IPv4 routes (Unicast): 512 IPv4 hosts: 4096 IPv4 routes (Multicast): 2048 Maximum of neighboring networks: 750 IPv6 routes (Unicast): 128 IPv6 hosts: 2048 IPv6 routes (Multicast): 1024 QoS hardware queues per port: 8 IGMP snooping entries: 1000 Virtual interfaces (VLANs): 2048
MAC Address Table Size	16000 entries
Jumbo Frame Support	9216 bytes
Routing Protocol	RIP-1, RIP-2, OSPFv3, static IPv4 routing, static IPv6 routing, RIPng, CIDR
Remote Management Protocol	SNMP 1, RMON 1, RMON 2, SNMP, RMON 3, RMON 9, Telnet, SNMP 3, SNMP 2c, HTTP, HTTPS, TFTP, SSH, CLI
Features	BOOTP support, RARP support, ARP support, VLAN support, auto-uplink (auto MDI/MDI-X), DoS attack prevention, port mirroring, DiffServ support, store and forward, High Availability, SNTP support, sFlow, Spanning Tree Protocol (STP) support, Rapid Spanning Tree Protocol (RSTP) support, VLAN Stacking, Multiple Spanning Tree Protocol (MSTP) support, DHCP snooping, Access Control List (ACL) support, Quality of Service (QoS), IP Precedence, DHCP server, DHCP proxy, Dynamic ARP Inspection (DAI), temperature sensor, Redundant trunk group (RTG), Per-VLAN Spanning Tree Plus (PVST+), Cable Diagnostics Function, fanless, DHCP relay, port based access control, DHCP client, Energy Efficient Ethernet, Management Information Base (MIB), Multiple VLAN Registration Protocol (MVRP), Neighbor Discovery Protocol (NDP), NTP time synchronization, Class of Service (CoS), Strict Priority (SP), tagged VLAN, Captive Portal, DiffServ Code Point (DSCP) support, Smoothed Deficit Weighted Round Robin (SDWRR), system log, Internet Control Message Protocol (ICMP), ICMP Router Discovery Protocol (IRDP), Secure Copy (SCP), Management Information Base (MIB) II
Compliant Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3z, IEEE 802.1D, IEEE 802.1Q, IEEE 802.3ab, IEEE 802.1p, IEEE 802.3ad (LACP), IEEE 802.1w, IEEE 802.1x, IEEE 802.1s, IEEE 802.3ah, IEEE 802.1ab (LLDP), IEEE 802.1ak, IEEE 802.1BR
Dimensions (WxDxH)	11 in x 9.4 in x 1.7 in
Weight	5.47 lbs